

Connecting via Winsock to STN

Welcome to STN International! Enter x:x

LOGINID:sssptal202jxp

PASSWORD:

TERMINAL (ENTER 1, 2, 3, OR ?):2

* * * * * Welcome to STN International * * * * *

NEWS 1 Web Page URLs for STN Seminar Schedule - N. America
NEWS 2 "Ask CAS" for self-help around the clock
NEWS 3 JUL 20 Powerful new interactive analysis and visualization software,
STN AnaVist, now available
NEWS 4 AUG 11 STN AnaVist workshops to be held in North America
NEWS 5 AUG 30 CA/CAPLUS - Increased access to 19th century research documents
NEWS 6 AUG 30 CASREACT - Enhanced with displayable reaction conditions
NEWS 7 SEP 09 ACD predicted properties enhanced in REGISTRY/ZREGISTRY
NEWS 8 OCT 03 MATHDI removed from STN
NEWS 9 OCT 04 CA/CAPLUS-Canadian Intellectual Property Office (CIPO) added
to core patent offices
NEWS 10 OCT 06 STN AnaVist workshops to be held in North America
NEWS 11 OCT 13 New CAS Information Use Policies Effective October 17, 2005
NEWS 12 OCT 17 STN(R) AnaVist(TM), Version 1.01, allows the export/download
of CAPLUS documents for use in third-party analysis and
visualization tools
NEWS 13 OCT 27 Free KWIC format extended in full-text databases
NEWS 14 OCT 27 DIOGENES content streamlined
NEWS 15 OCT 27 EPFULL enhanced with additional content

NEWS EXPRESS JUNE 13 CURRENT WINDOWS VERSION IS V8.0, CURRENT
MACINTOSH VERSION IS V6.0c(ENG) AND V6.0Jc(JP),
AND CURRENT DISCOVER FILE IS DATED 13 JUNE 2005

NEWS HOURS STN Operating Hours Plus Help Desk Availability
NEWS INTER General Internet Information
NEWS LOGIN Welcome Banner and News Items
NEWS PHONE Direct Dial and Telecommunication Network Access to STN
NEWS WWW CAS World Wide Web Site (general information)

Enter NEWS followed by the item number or name to see news on that
specific topic.

All use of STN is subject to the provisions of the STN Customer
agreement. Please note that this agreement limits use to scientific
research. Use for software development or design or implementation
of commercial gateways or other similar uses is prohibited and may
result in loss of user privileges and other penalties.

* * * * * STN Columbus * * * * *

FILE 'HOME' ENTERED AT 08:53:15 ON 30 OCT 2005

=> file caplus

COST IN U.S. DOLLARS

FULL ESTIMATED COST

SINCE FILE	TOTAL
ENTRY	SESSION
0.21	0.21

FILE 'CAPLUS' ENTERED AT 08:53:26 ON 30 OCT 2005
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.
COPYRIGHT (C) 2005 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 30 Oct 2005 VOL 143 ISS 19
FILE LAST UPDATED: 28 Oct 2005 (20051028/ED)

Effective October 17, 2005, revised CAS Information Use Policies apply. They are available for your review at:

<http://www.cas.org/infopolicy.html>

```
=> s natural gas (1) hydrogen (1) carbon monoxide (1) carbon dioxide
    665664 NATURAL
      35 NATURALS
    665685 NATURAL
      (NATURAL OR NATURALS)
    1460335 GAS
    496679 GASES
    1637697 GAS
      (GAS OR GASES)
    68229 NATURAL GAS
      (NATURAL (W) GAS)
    892941 HYDROGEN
    5638 HYDROGENS
    896109 HYDROGEN
      (HYDROGEN OR HYDROGENS)
    1152276 CARBON
    25288 CARBONS
    1161370 CARBON
      (CARBON OR CARBONS)
    170064 MONOXIDE
    982 MONOXIDES
    170583 MONOXIDE
      (MONOXIDE OR MONOXIDES)
    143931 CARBON MONOXIDE
      (CARBON (W) MONOXIDE)
    1152276 CARBON
    25288 CARBONS
    1161370 CARBON
      (CARBON OR CARBONS)
    444036 DIOXIDE
    6518 DIOXIDES
    445689 DIOXIDE
      (DIOXIDE OR DIOXIDES)
    209897 CARBON DIOXIDE
      (CARBON (W) DIOXIDE)
L1      74 NATURAL GAS (L) HYDROGEN (L) CARBON MONOXIDE (L) CARBON DIOXIDE

=> s 11 and remov? (5a) carbon dioxide
    1182637 REMOV?
    1152276 CARBON
```

25288 CARBONS
 1161370 CARBON
 (CARBON OR CARBONS)
 444036 DIOXIDE
 6518 DIOXIDES
 445689 DIOXIDE
 (DIOXIDE OR DIOXIDES)
 209897 CARBON DIOXIDE
 (CARBON(W)DIOXIDE)
 7313 REMOV? (5A) CARBON DIOXIDE
 L2 7 L1 AND REMOV? (5A) CARBON DIOXIDE

 => s 11 and separat? (5a) carbon dioxide
 336919 SEPARAT?
 273731 SEP
 12583 SEPS
 285122 SEP
 (SEP OR SEPS)
 446082 SEPD
 1 SEPDS
 446083 SEPD
 (SEPD OR SEPDS)
 91823 SEPG
 1 SEPGS
 91824 SEPG
 (SEPG OR SEPGS)
 555054 SEPN
 35972 SEPNS
 573253 SEPN
 (SEPN OR SEPNS)
 1364373 SEPARAT?
 (SEPARAT? OR SEP OR SEPD OR SEPG OR SEPN)
 1152276 CARBON
 25288 CARBONS
 1161370 CARBON
 (CARBON OR CARBONS)
 444036 DIOXIDE
 6518 DIOXIDES
 445689 DIOXIDE
 (DIOXIDE OR DIOXIDES)
 209897 CARBON DIOXIDE
 (CARBON(W)DIOXIDE)
 3504 SEPARAT? (5A) CARBON DIOXIDE
 L3 6 L1 AND SEPARAT? (5A) CARBON DIOXIDE

 => s 12 and 13
 L4 1 L2 AND L3

 => s 12 or 13
 L5 12 L2 OR L3

 => s 15 and fischer tropsch
 23089 FISCHER
 15 FISCHERS
 23101 FISCHER
 (FISCHER OR FISCHERS)
 7737 TROPSCH
 7637 FISCHER TROPSCH
 (FISCHER(W)TROPSCH)
 L6 0 L5 AND FISCHER TROPSCH

 => s 15 and adjust?
 251275 ADJUST?
 L7 0 L5 AND ADJUST?

=> D L5 IBIB AB 1-12

L5 ANSWER 1 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2004:691478 CAPLUS
DOCUMENT NUMBER: 141:192262
TITLE: Methanol plant retrofit for the manufacture of acetic acid
INVENTOR(S): Vidalin, Kenneth Ebenes; Thiebaut, Daniel Marcel
PATENT ASSIGNEE(S): Acetex Cyprus Limited, Cyprus
SOURCE: U.S., 16 pp., Cont.-in-part of U.S. 6,232,352.
CODEN: USXXAM
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 3
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 6781014	B1	20040824	US 2002-129038	20020430
US 6274096	B1	20010814	US 1999-430888	19991101
US 6232352	B1	20010515	US 2000-547831	20000412
WO 2001032594	A1	20010510	WO 2000-CY4	20001031

W: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM

RW: GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG

PRIORITY APPLN. INFO.:
US 1999-430808 A2 19991101
US 1999-430888 A2 19991101
US 2000-547831 A2 20000412
WO 2000-CY4 W 20001031

AB The retrofitting of an existing methanol or methanol/ammonia plant to make acetic acid is described. The existing plant has a reformer into which natural gas or another hydrocarbon and steam (water) are fed. Synthesis gas is formed in the reformer. All or part of the synthesis gas is processed to sep. out carbon dioxide, carbon monoxide and hydrogen, and the sepd. carbon dioxide is the exiting to the existing methanol synthesis loop for methanol synthesis, or back into the feed to the reformer to enhance carbon monoxide formation in the synthesis gas. Any remaining synthesis gas not fed into the carbon dioxide separator can be converted to methanol in the existing methanol synthesis loop along with carbon dioxide from the separator and/or imported carbon dioxide, and hydrogen from the separator. The separated carbon monoxide is then reacted with methanol to produce acetic acid or an acetic acid precursor by a conventional process.

REFERENCE COUNT: 40 THERE ARE 40 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L5 ANSWER 2 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2002:555943 CAPLUS
DOCUMENT NUMBER: 137:127091
TITLE: Bimodal hydrogen manufacture
INVENTOR(S): Vidalin, Kenneth Ebenes
PATENT ASSIGNEE(S): Can.
SOURCE: U.S. Pat. Appl. Publ., 15 pp.
CODEN: USXXCO

DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 2002098132	A1	20020725	US 2001-768030	20010122
US 6599491	B2	20030729		

PRIORITY APPLN. INFO.: US 2001-768030 20010122

AB The converting of an existing methanol plant to make hydrogen and optionally methanol is disclosed. The converted plant utilizes the steam reformer to which (a) a hydrocarbon, e.g., natural gas, or a lower alkanol, e.g., methanol, and (b) steam (water) are fed. Syngas is formed in the reformer. All or part of the syngas is processed in a CO converter and/or a sepn. unit to sep. out carbon dioxide, carbon monoxide and hydrogen. In the first mode, the CO converter is isolated and the sepd. carbon dioxide is fed either to the existing methanol synthesis loop for methanol synthesis, or back into the feed to the reformer to enhance carbon monoxide formation in the syngas. In the second mode, a lower alkanol is fed to the reformer, and the methanol synthesis loop is shutdown and isolated from the rest of the plant. Any remaining syngas not fed to the carbon dioxide separator can be converted to methanol in the existing methanol synthesis loop along with carbon dioxide from the separator and/or imported carbon dioxide, and hydrogen from the separator. In the second mode, the separated carbon monoxide is preferably recycled to the reformer and/or to the CO converter to enhance hydrogen production

L5 ANSWER 3 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2002:505214 CAPLUS
DOCUMENT NUMBER: 137:64902
TITLE: Bimodal acetic acid manufacture in methanol plants
INVENTOR(S): Vidalin, Kenneth Ebenes
PATENT ASSIGNEE(S): USA
SOURCE: U.S. Pat. Appl. Publ., 22 pp.
CODEN: USXXCO

DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 2002085963	A1	20020704	US 2000-751240	20001229
US 6531630	B2	20030311		

PRIORITY APPLN. INFO.: US 2000-751240 20001229

AB The converting of an existing methanol plant to make acetic acid is disclosed. The converted plant utilizes a steam reformer to which (a) a hydrocarbon, e.g., natural gas, or a lower alkanol, e.g., methanol, and (b) steam (water) are fed. Syngas is formed in the reformer. All or part of the syngas is processed to sep. out carbon dioxide, carbon monoxide and hydrogen, and the sepd. carbon dioxide is fed either to the existing methanol synthesis loop for methanol synthesis, or back into the feed to the reformer to enhance carbon monoxide formation in the syngas. When a lower alkanol is fed to the reformer, the methanol synthesis loop is shutdown and isolated from the rest of the plant. Any remaining syngas not fed to the carbon dioxide separator can be converted to methanol in the existing methanol synthesis loop along with carbon

dioxide from the separator and/or imported carbon dioxide, and hydrogen from the separator. The separated carbon monoxide is then reacted with the methanol to produce acetic acid or an acetic acid precursor by a conventional process. When the methanol synthesis loop is shutdown, an imported source of methanol is used.

L5 ANSWER 4 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2002:363425 CAPLUS
DOCUMENT NUMBER: 136:373828
TITLE: Carbon dioxide capture process with regenerable sorbents
INVENTOR(S): Pennline, Henry W.; Hoffman, James S.
PATENT ASSIGNEE(S): United States Dept. of Energy, USA
SOURCE: U.S., 5 pp.
CODEN: USXXAM
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 6387337	B1	20020514	US 2000-616871	20000714
PRIORITY APPLN. INFO.:			US 2000-616871	20000714

AB A process to remove carbon dioxide from a gas stream using a cross-flow, or a moving-bed reactor. In the reactor the gas contacts an active material that is an alkali-metal compound, such as an alkali-metal carbonate, alkali-metal oxide, or alkali-metal hydroxide; or in the alternative, an alkaline-earth metal compound, such as an alkaline-earth metal carbonate, alkaline-earth metal oxide, or alkaline-earth metal hydroxide. The active material can be used by itself or supported on a substrate of carbon, alumina, silica, titania or aluminosilicate. When the active material is an alkali-metal compound, the carbon-dioxide reacts with the metal compound to generate bicarbonate. When the active material is an alkaline-earth metal, the carbon dioxide reacts with the metal compound to generate carbonate. Spent sorbent containing the bicarbonate or carbonate is moved to a second reactor where it is heated or treated with a reducing agent such as, natural gas, methane, carbon monoxide hydrogen, or a synthesis gas comprising of a combination of carbon monoxide and hydrogen. The heat or reducing agent releases carbon dioxide gas and regenerates the active material for use as the sorbent material in the first reactor. New sorbent may be added to the regenerated sorbent prior to subsequent passes in the carbon dioxide removal reactor.

REFERENCE COUNT: 7 THERE ARE 7 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L5 ANSWER 5 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2002:138940 CAPLUS
DOCUMENT NUMBER: 136:202908
TITLE: Method of manufacturing synthesis gas
INVENTOR(S): Iijima, Masaki; Kobayashi, Kazuto; Morita, Kazuhiro
PATENT ASSIGNEE(S): Mitsubishi Heavy Industries, Ltd., Japan
SOURCE: Eur. Pat. Appl., 10 pp.
CODEN: EPXXDW
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
EP 1180544	A2	20020220	EP 2001-105475	20010314
EP 1180544	A3	20030226		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, SI, LT, LV, FI, RO				
JP 2002060203	A2	20020226	JP 2000-246913	20000816
US 2002024038	A1	20020228	US 2001-801720	20010309
US 6726852	B2	20040427		
ZA 2001002066	A	20010913	ZA 2001-2066	20010313
AU 744233	B1	20020221	AU 2001-28018	20010316
NO 2001001753	A	20020218	NO 2001-1753	20010406
RU 2258029	C2	20050810	RU 2001-110186	20010413
PRIORITY APPLN. INFO.:			JP 2000-246913	A 20000816

AB A method of manufacturing a synthesis gas containing hydrogen and carbon monoxide comprises the steps of removing only hydrogen sulfide from a natural gas containing hydrogen sulfide and carbon dioxide by permitting the natural gas to pass through a hydrogen sulfide-removing device filled with a hydrogen sulfide absorbent, adding carbon dioxide and steam to the natural gas which the hydrogen sulfide has been removed to prepare a mixed gas, and feeding the mixed gas into a reaction tube of a reformer, thereby permitting mainly a steam reforming reaction to take place in the mixed gas. This method enables hydrogen sulfide in natural gas to be removed while permitting the carbon dioxide of natural gas to be effectively used, thereby reducing the quantity of carbon dioxide to be added to the natural gas to be transferred to the reformer.

L5 ANSWER 6 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN
 ACCESSION NUMBER: 2001:352292 CAPLUS
 DOCUMENT NUMBER: 134:328212
 TITLE: Methanol plant retrofit for acetic acid manufacture
 INVENTOR(S): Vidalin, Kenneth Ebenes
 PATENT ASSIGNEE(S): Acetex Limited, Cyprus
 SOURCE: U.S., 17 pp., Cont.-in-part of U.S. Ser. No. 430,888.
 CODEN: USXXAM
 DOCUMENT TYPE: Patent
 LANGUAGE: English
 FAMILY ACC. NUM. COUNT: 3
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 6232352	B1	20010515	US 2000-547831	20000412
US 6274096	B1	20010814	US 1999-430888	19991101
CA 2388961	AA	20010510	CA 2000-2388961	20001031
WO 2001032594	A1	20010510	WO 2000-CY4	20001031
W: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM				
RW: GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG				
EP 1226103	A1	20020731	EP 2000-972559	20001031
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, SI, LT, LV, FI, RO, MK, CY, AL				
NZ 519314	A	20031031	NZ 2000-519314	20001031
RU 2250894	C2	20050427	RU 2002-114828	20001031

AU 781369	B2	20050519	AU 2001-11278	20001031
US 6353133	B1	20020305	US 2001-851915	20010509
NO 2002002063	A	20020626	NO 2002-2063	20020430
US 6781014	B1	20040824	US 2002-129038	20020430
PRIORITY APPLN. INFO.:			US 1999-430888	A2 19991101
			US 1999-430808	A2 19991101
			US 2000-547831	A 20000412
			WO 2000-CY4	W 20001031

AB The retrofitting of an existing methanol or methanol/ammonia plant to make acetic acid is disclosed. The existing plant has a reformer to which natural gas or another hydrocarbon and steam (water) are fed for the generation of synthesis gas (i.e., CO, H₂, CO₂) via steam reforming. All or part of the produced synthesis gas is processed to sep. out carbon dioxide, carbon monoxide, and hydrogen, and the sepd. carbon dioxide is fed either to the existing methanol synthesis loop for methanol synthesis, or back into the feed to the reformer to enhance carbon monoxide formation in the synthesis gas. Any remaining synthesis gas not fed to the carbon dioxide separator can be converted to methanol by hydrogenation in the existing methanol synthesis loop along with carbon dioxide from the separator and/or imported carbon dioxide, and hydrogen from the separator. The separated carbon monoxide is then reacted with the methanol to produce acetic acid or an acetic acid precursor by a conventional process.

REFERENCE COUNT: 16 THERE ARE 16 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L5 ANSWER 7 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 2001:338470 CAPLUS

DOCUMENT NUMBER: 134:328210

TITLE: Methanol plant retrofit for the manufacture of acetic acid

INVENTOR(S): Thiebaut, Daniel Marcel; Vidalin, Kenneth Ebennes

PATENT ASSIGNEE(S): Acetex (Cyprus) Limited, Cyprus

SOURCE: PCT Int. Appl., 44 pp.

CODEN: PIXXD2

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 3

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 2001032594	A1	20010510	WO 2000-CY4	20001031
W:			AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM	
RW:			GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG	
US 6274096	B1	20010814	US 1999-430888	19991101
US 6232352	B1	20010515	US 2000-547831	20000412
CA 2388961	AA	20010510	CA 2000-2388961	20001031
EP 1226103	A1	20020731	EP 2000-972559	20001031
R:			AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, SI, LT, LV, FI, RO, MK, CY, AL	
NZ 519314	A	20031031	NZ 2000-519314	20001031
RU 2250894	C2	20050427	RU 2002-114828	20001031
AU 781369	B2	20050519	AU 2001-11278	20001031

NO 2002002063	A	20020626	NO 2002-2063	20020430
US 6781014	B1	20040824	US 2002-129038	20020430
PRIORITY APPLN. INFO.:			US 1999-430888	A 19991101
			US 2000-547831	A 20000412
			US 1999-430808	A2 19991101
			WO 2000-CY4	W 20001031

AB The retrofitting of an existing methanol or methanol/ammonia plant to make acetic acid is disclosed. The existing plant has a reformer to which natural gas or another hydrocarbon and steam (water) are fed and synthesis gas produced. All or part of the synthesis gas is processed to sep. out carbon dioxide, carbon monoxide, and hydrogen, and the sepd. carbon dioxide is fed either to the existing methanol synthesis loop for methanol synthesis, or back into the feed to the reformer to enhance the amount of carbon monoxide formation in the synthesis gas. Any remaining synthesis gas not fed to the carbon dioxide separator can be converted to methanol in the existing methanol synthesis loop along with carbon dioxide from the separator and/or imported carbon dioxide, and hydrogen from the separator. The separated carbon monoxide is then reacted with the methanol to produce acetic acid or an acetic acid precursor by a conventional process. Also disclosed is the reaction of separated hydrogen with nitrogen, in a conventional manner, to produce ammonia and the reaction of a portion of the acetic acid in a conventional manner with oxygen and ethylene to form vinyl acetate. The nitrogen for the added ammonia capacity in a retrofit of an original methanol plant comprising an ammonia synthesis loop and the oxygen for the vinyl acetate process are obtained from a new air separation unit; process flow diagrams are presented.

REFERENCE COUNT: 3 THERE ARE 3 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L5 ANSWER 8 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 1999:595550 CAPLUS
DOCUMENT NUMBER: 131:247527
TITLE: Meeting CO2 demands
AUTHOR(S): Alderton, P. D.
CORPORATE SOURCE: Foster Wheeler Petroleum Development Ltd, UK
SOURCE: Hydrocarbon Engineering (1999), 4(7), 50-52
CODEN: HYENF5
PUBLISHER: Palladian Publications Ltd
DOCUMENT TYPE: Journal
LANGUAGE: English

AB Use of pre-combustion carbon removal from natural gas used by power generation plants is described as a method for meeting demands for reduced CO2 levels. A viable process was developed first for a new land-based power station, and then for a typical offshore oil production platform. The natural gas is not used directly as fuel in the gas turbine, but is fed initially to a catalytic partial oxidation reactor where the carbon in the natural gas is converted to carbon dioxide using air as the oxidant. The carbon monoxide is, in turn, converted to carbon dioxide which is then removed and the resulting hydrogen-rich gas is used as fuel in the gas turbine. A CO2 capture of 90% or greater can be achieved. The extracted CO2 can be injected into an oil reservoir to enhance oil recovery or used as a product in its own right.

REFERENCE COUNT: 1 THERE ARE 1 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L5 ANSWER 9 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 1997:776847 CAPLUS
DOCUMENT NUMBER: 127:360662

TITLE: Method and apparatus for manufacture of high-purity hydrogen by steam conversion of natural gas, conversion of carbon monoxide to carbon dioxide, removal of carbon dioxide, and diffusion of hydrogen through palladium membrane

INVENTOR(S): Budanichev, Sergej A.; Guk, Yuriy N.; Kadnikov, Valerij P.; Kirnos, Igor V.; Klyshnikov, Sergej T.; Kukuĭ, Boris G.

PATENT ASSIGNEE(S): Sovmestnoe Predpriyatie Uralskij Nauchno-Inzhenernyj Tsentr "vodorod", Russia

SOURCE: Russ. From: Izobreteniya 1997, (21), 262.
CODEN: RUXXE7

DOCUMENT TYPE: Patent

LANGUAGE: Russian

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
RU 2085476	C1	19970727	RU 1993-21176	19930422
PRIORITY APPLN. INFO.:			RU 1993-21176	19930422
AB Title only translated.				

L5 ANSWER 10 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 1997:397685 CAPLUS

DOCUMENT NUMBER: 127:17415

TITLE: Process for producing syngas and hydrogen from natural gas using a membrane reactor

INVENTOR(S): Galuszka, Jan Z.; Fouda, Safaa; Pandey, Raj N.; Ahmed, Shamsuddin

PATENT ASSIGNEE(S): Natural Resources Canada, Can.

SOURCE: U.S., 7 pp.
CODEN: USXXAM

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 5637259	A	19970610	US 1995-567102	19951204
CA 2190893	AA	19970605	CA 1996-2190893	19961121
CA 2190893	C	20000111		

PRIORITY APPLN. INFO.: US 1995-567102 A 19951204

AB A procedure for the production of synthesis gas and hydrogen from natural gas is described. The procedure includes: (a) providing a double tubular hydrogen-transfer reactor having an inner tubular wall defining a heated reaction zone containing a catalyst and an outer tubular wall defining an annular zone between the tubular walls, the inner tubular wall including a hydrogen semipermeable membrane portion adapted to permit diffusion of hydrogen through from the reaction zone to the annular zone while being impervious to other gases, (b) passing through the catalytic reaction zone a feedstock comprising a mixture of methane and oxygen or a mixture of methane and carbon dioxide or a mixture of methane, carbon dioxide and oxygen, (c) continuously removing from the reaction zone at least part of the hydrogen being formed by diffusion through the hydrogen semipermeable membrane into the annular zone, (d) continuously removing diffused hydrogen from the annular zone, and (e) continuously removing a product mixture of carbon monoxide and hydrogen from the reaction zone. An apparatus diagram is presented.

L5 ANSWER 11 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 1989:556920 CAPLUS
DOCUMENT NUMBER: 111:156920
TITLE: Production and recovery of hydrogen and carbon
monoxide
INVENTOR(S): Nicholas, David M.; Goff, Stephen P.; Roden, Thomas
M.; Bushinsky, Joseph P.
PATENT ASSIGNEE(S): Air Products and Chemicals, Inc., USA
SOURCE: U.S., 13 pp.
CODEN: USXXAM
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
-----	---	-----	-----	-----
US 4836833	A	19890606	US 1988-157434	19880217
PRIORITY APPLN. INFO.:			US 1988-157434	19880217
OTHER SOURCE(S):	CASREACT 111:156920			

AB A method for separating and recovering of high-purity H₂ and CO from a gas mixture containing H₂, CO, CO₂, and CH₄ (e.g. synthesis gas obtained in steam reforming of hydrocarbons) comprises passing the gas mixture at superatm. pressure through a solid adsorbent bed to remove CO₂ by pressure-swing adsorption (PSA), purifying the CO₂-free primary effluent by selective adsorption of CO in a 2nd adsorbent bed by PSA, and passing the gas stream through a series of selective semi-permeable membranes to recover a permeated stream of high-purity H₂ (≥99 mol.%) and a non-permeated stream comprising ≥85 mol.% CO. The method gives high product yields, and has significantly reduced capital and operation costs.

L5 ANSWER 12 OF 12 CAPLUS COPYRIGHT 2005 ACS on STN

ACCESSION NUMBER: 1974:523933 CAPLUS
DOCUMENT NUMBER: 81:123933
TITLE: Low-temperature processes for purifying hydrogen and
carbon monoxide feedstocks for industrial chemical
products
AUTHOR(S): Tanz, Heiner
CORPORATE SOURCE: Messer Griesheim G.m.B.H., Frankfurt, Fed. Rep. Ger.
SOURCE: Progr. Refrig. Sci. Technol., Proc. Int. Congr.
Refrig., 13th (1973), Meeting Date 1971, Volume 1,
619-25. Editor(s): Pentzer, W. T. Avi: Westport,
Conn.
CODEN: 28FQAP
DOCUMENT TYPE: Conference
LANGUAGE: English

AB Compared to naphtha, natural gas is less desirable for the production of CO-enriched gases because of its low C/H ratio. By new processes such as CO production by reforming and low-temperature separation, natural gas can be made into a desirable feedstock for the production of CO-enriched gases. Low-temperature gas-separation plants for the purification of H and CO and the removal of CO₂ and N from natural gas are described.

WEST Search History

[Hide Items](#)[Restore](#)[Clear](#)[Cancel](#)

DATE: Sunday, October 30, 2005

Hide?	<u>Set</u> <u>Name</u>	<u>Query</u>	<u>Hit</u> <u>Count</u>
		<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI; THES=ASSIGNEE; PLUR=YES; OP=ADJ</i>	
<input type="checkbox"/>	L7	L5 and hydrogen with fuel	17
<input type="checkbox"/>	L6	L5 and hydrogen with fuel with reform\$3	4
<input type="checkbox"/>	L5	L4 and fischer tropsch	29
<input type="checkbox"/>	L4	L2 and (remov\$3 or separat\$3)with carbon dioxide	52
<input type="checkbox"/>	L3	L2 and (remov\$3 or separat\$3)nea5 carbon dioxide	0
<input type="checkbox"/>	L2	L1 and adjust\$3 near4 (syngas or synthesis gas or hydrogen near3 carbon monoxide)	71
<input type="checkbox"/>	L1	natural gas same hydrogen with carbon monoxide with carbon dioxide and (steam near3 reform\$3 or autothermal reform\$3)	754

END OF SEARCH HISTORY